


Wilcoxon Research

Model 731-207 Ultra low frequency seismic accelerometer



Features

- Compact construction to fit in tight spaces
- Ultra-high sensitivity
- Ultra low-noise electronics for clear signals at very low vibration levels
- Reverse wiring protection



Dynamic

Sensitivity, ±10%, 25°C	10 V/g
Acceleration range.....	0.5 g peak
Amplitude nonlinearity.....	1%
Frequency response, nominal:	
±5%	0.6 - 650 Hz
±10%	0.5 - 850 Hz
±3 dB.....	0.2 - 1,300 Hz
Resonance frequency, mounted, nominal.....	2.4 kHz
Transverse sensitivity, max.	1% of axial
Temperature response:	
-0°C	-18%
+80°C	+8%

Electrical

Power requirement: voltage source.....	18 - 30 VDC
current regulating diode.....	2 - 10 mA
Electrical noise, equiv. g, nominal:	
Broadband 2.5 Hz to 25 kHz.....	2 µg
Spectral 2 Hz.....	0.28 µg/√Hz
10 Hz.....	0.09 µg/√Hz
100 Hz.....	0.03 µg/√Hz
Output impedance, max.....	500 Ω
Bias output voltage, nominal.....	10 VDC
Grounding	case grounded

Environmental

Temperature range.....	0 to 80°C
Vibration limit	50 g peak
Shock limit.....	250 g peak
Electromagnetic sensitivity @ 60 Hz.....	20 µg/gauss
Sealing	hermetic
Base strain sensitivity	0.0005 g/µstrain

Physical

Weight	50 grams
Case material	316L stainless steel
Mounting	10-32 UNF
Output connector	10-32 coaxial
Recommended.....	J93

Accessories supplied: Calibration data; SF1 mounting stud
 Accessories available: R1-2-J93-10 cable assembly, magnetic mounting bases, SF5 cementing studs, SF4 isolation mounting base, signal conditioners



98069 Rev.C.3 12/07

Due to continued research and product development, Wilcoxon Research reserves the right to amend this specification without notice.



ALTHEN GmbH Mess- und Sensortechnik

Frankfurter Strasse 150 - 152
 65779 Kelkheim / Germany

phone: +49 (0)6195 70060
 fax: +49 (0)6195 700666

sales@althensensors.com
 www.althensensors.com